




## SBC-SAMA5D36 - Single Board Computer



SBC-SAMA5D36	
	
Operating system	Linux, Android on request
CPU manufacturer	MICROCHIP SAMA5D3
CPU architecture	ARM Cortex-A5
CPU performance	536 MHz - 850 DMIPS
Co-Processor	ARM Neon™, FPU
RAM	up to 512 MByte DDR2 SDRAM
Flash	up to 32 MByte NOR-Flash, up to 2048 MByte NAND-Flash
Ethernet	1x 10/100Base TX, 1x 10/100/1000Base TX both with RJ45 connector
UART: RS232/LVTTL/IrDA	0 / 5 / 4
USB Host	2x USB Host 2.0 high speed on USB-A connector
USB Device	1x USB Device 2.0 high speed on MicroUSB connector
Analog Audio	SSI interface
LCD interface	up to XGA RGB (EDT connector) and DVI (HDMI-connector)
Touch	4-wire resistive, optional capacitive
CAN	2 x 2.0 A/B (LVTTTL)
I2C	3
SPI	1 (+4 optional)
Digital GPIO	up to 52
MMC/SDC	1x microSD, 1x on Extension Header
PWM	2
Analog Input	5
User Buttons	2
User LEDs	4
RTC (battery buffered)	yes, with battery holder (CR1225)
Size in mm	74 x 135 x 15
Power Supply	5V via 2mm Power Jack / 5V via USB connector / Lithium Battery (charger onboard)
max. power consumption	5V @ 300 mA max.
Operating temperature	0...+70°C, opt. -40...+85°C
Casing	optional available
Developer kits available	yes
Custom specific solutions	yes

Subject to change without notice.  
RevZ: 03/2019



**emtrion GmbH**  
Alter Schlachthof 45  
D-76131 Karlsruhe  
Tel. +49 (0) 721 62725-0  
Fax +49 (0) 721 62725-19  
E-Mail sales@emtrion.com

Visit us online at:  
[www.emtrion.com](http://www.emtrion.com)